

Rundstangen gezogen aus Wieland-Messing



Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranz	Enden-ausführung
Wieland Z33, CuZn39Pb3, EN 12164 Präzisionsstange W5000, 3.000 ± 30 mm						
2,0	0,027	●	441302000	R600	h8	angefast/angespitzt
2,5	0,042	●	441302500			
3,0	0,060	●	441303000			
3,5	0,082	●	441303500			
4,0	0,107	●	441304000			
4,2	0,118	●	441304200			
4,5	0,135	●	441304500			
5,0	0,167	●	441305000			
5,5	0,202	●	441305500			
6,0	0,240	●	441306000			
6,5	0,282	●	441306500			
7,0	0,327	●	441307000			
7,5	0,376	●	441307500			
8,0	0,427	●	441508000			
8,5	0,482	●	441508500			
9,0	0,541	●	441509000			
9,5	0,603	●	441509500			
10,0	0,668	○	441510000			
10,5	0,737	○	441510500			
11,0	0,808	○	441511000			
11,5	0,888	○	441511500			
12,0	0,961	○	441512000			
12,5	1,040	○	441512500			
13,0	1,128	○	441513000			
13,5	1,220	○	441513500			
14,0	1,308	○	441514000			
14,5	1,400	○	441514500			
15,0	1,502	○	441515000			
15,5	1,608	○	441515500			
16,0	1,710	○	441516000			
16,5	1,824	○	441516500			
17,0	1,929	○	441517000			
17,5	2,052	○	441517500			
18,0	2,163	○	441518000			
18,5	2,228	○	441518500			
19,0	2,410	○	441519000			
19,5	2,544	○	441519500			
20,0	2,670	○	441520000			
20,5	2,812	○	441520500			
21,0	2,944	○	441521000			
22,0	3,231	○	441522000			
22,5	3,384	○	441522500			
23,0	3,552	○	441523000			
24,0	3,844	○	441524000			
25,0	4,160	○	441525000			
				R430		

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranz	Enden-ausführung
Wieland Z33, CuZn39Pb3, EN 12164 Präzisionsstange W5000, 3.000 ± 30 mm						
26,0	4,512	○	441526000	R430	h8	angefast/angespitzt
27,0	4,880	○	441527000			
28,0	5,232	○	441528000			
29,0	5,600	○	441529000			
30,0	6,008	○	441530000			
31,0	6,432	○	441531000			
32,0	6,840	○	441532000			
33,0	7,276	○	441533000			
34,0	7,716	○	441534000			
35,0	8,188	○	441535000			
36,0	8,652	○	441536000			
37,0	9,152	○	441537000			
38,0	9,640	○	441538000			
39,0	10,156	○	442139000			
40,0	10,688	○	442140000			
42,0	11,780	○	442142000			
44,0	12,920	○	442144000			
45,0	13,520	○	442145000			
46,0	14,130	○	442146000			
48,0	15,380	○	442148000			
50,0	16,690	○	442150000			
52,0	18,050	○	442152000			
55,0	20,190	○	442155000			
56,0	20,940	○	442156000			
58,0	22,460	○	442158000			
60,0	24,030	○	442160000			
65,0	28,210	○	442165000			
70,0	32,710	○	442170000			
75,0	37,552	○	442175000			
80,0	42,726	○	442180000			
				R360	h10	angefast/gesägt
				M	h11	gesägt/gesägt

