

Rundstangen gezogen aus Wieland-Messing

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranz	Enden- ausführung
mm	kg/m					
Wieland Z33, CuZn39Pb3, EN 12164 Präzisionsstange W5000, 3.975 ± 30 mm						
16,0	1,710	○	441616000	R430	h8	beidseitig angefast
17,5	2,052	○	441617500			
18,0	2,163	○	441618000			
21,0	2,944	○	441621000			
24,0	3,844	○	441624000			
29,0	5,600	○	441629000			
30,0	6,008	○	441630000			

Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranz	Enden- ausführung
mm	kg/m					
Wieland Z32, CuZn39Pb3, EN 12164 Triebscheiblequalität, 3.000 ± 30 mm						
3,0	0,060	●	444103000	R430	B	angefast/angespitzt
4,0	0,107	●	444104000			
5,0	0,167	●	444105000			
6,0	0,240	●	444106000			
6,5	0,282	●	444106500			
7,0	0,327	●	444107000			
7,5	0,376	●	444107500			
8,0	0,427	●	444108000			
8,5	0,482	●	444108500			
9,0	0,541	●	444109000			
10,0	0,668	●	444110000			
11,0	0,808	○	444111000			
12,0	0,961	○	444112000			
13,0	1,128	○	444113000			
14,0	1,308	○	444114000			

Standardverpackung: ● = in Holzkisten von ca. 500 kg,
 ≤ 5,5 mm in Kleinbunden von 25 kg
 ○ = in Bunden von ca. 500 kg, alternativ
 in Bunden von ca. 1.000 kg möglich
 □ = auf Palette bis zu 1.500 kg

Rundstangen gezogen aus Wieland-Messing



Abmessung	Gewicht	Verpackung	Material-Nr.	Zustand	Toleranzklasse	Enden- ausführung
mm	kg/m					
Wieland Z21, CuZn38Pb2, EN 12164 3.000 ± 30 mm						
2,5	0,041	●	443302500	R410	B	angefast/angespitzt
3,0	0,059	●	443303000			
3,5	0,081	●	443303500			
4,0	0,106	●	443304000			
4,5	0,134	●	443304500			
4,8	0,152	●	443304800			
5,0	0,165	●	443305000			
5,5	0,200	●	443305500			
6,0	0,238	●	443306000			
6,5	0,279	●	443306500			
7,0	0,323	●	443307000			
7,5	0,371	●	443307500			
8,0	0,422	●	443308000			
8,5	0,477	●	443308500			
9,0	0,534	●	443309000			
10,0	0,660	●	443310000			
11,0	0,798	○	443311000			
12,0	0,950	○	443312000			
13,0	1,115	○	443313000			
14,0	1,293	○	443314000			
15,0	1,484	○	443315000			
16,0	1,689	○	443316000			
17,0	1,907	○	443317000			
18,0	2,138	○	443318000			
20,0	2,639	○	443320000			
22,0	3,193	○	443322000			
30,0	5,938	○	443330000			